

Type : 3EL112M4D-PD-B0-000

Date : 01.01.2023

Power [kW]	: 4.00	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 112M
Pole Number	: 4	Weight [kg]	: 32.6
Nominal Speed [rpm]	: 1460	Insulation Class	: F [155°C]
Nominal Current [A]	: 8.05	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 26.2	Protection Class	: IP55
Nominal Efficiency [η]	: 88.6	Vibration Severity Grade	: A
Power Factor [cosφ]	: 0.81	Method of Cooling	: IC411 (TEFC)
Locked Rotor Current [Ia/In]	: 7.4	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.8	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.8	Motor Thermal Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 58

### ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	Cosφ	Cl
Δ	400	50	4.00	1460	8.05	88.6	88.4	87.5	0.81	IE3
Y	690	50	4.00	1460	4.65	88.6	88.4	87.5	0.81	IE3
Δ	460	60	4.00	1765	6.98	89.5	89.9	88.9	0.80	IE3
Δ	460	60	4.55	1755	7.78	89.5	89.4	88.0	0.82	IE3


### MECHANICAL DATA

Moment of Inertia [kgm <sup>2</sup> ]	: 0.01437
Bearing [DS / NS]	: 6206ZZ / 6206ZZ
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

### TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M25x1.5
Terminal Box Blind Cap	: M25x1.5
Contact Screw Thread	: M5

### MECHANICAL DIMENSIONS



Manufactured and tested in accordance with IEC 60034

\*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

\*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.  
www.elkmotor.com.tr  
+90 (282) 726 92 94

## TECHNICAL DATASHEET ACCORDING TO COMMISSION REGULATION (EU) 2019/1781 THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EL112M4D-PD-B0-000

Date : 01.01.2023


### NAMEPLATE DATA

Power [kW]	: 4.00	Nominal Speed [rpm]	: 1460
Nominal Voltage [V]	: 400	Nominal Current [A]	: 8.05
Connection Type [ $\Delta$ / Y]	: $\Delta$	Nominal Moment [Nm]	: 26.2
Nominal Frequency [Hz]	: 50	Nominal Efficiency [ $\eta$ %]	: 88.6

### THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed $n/n_N$ [%]	Torque $T/T_N$ [%]	Relative Power Losses $P_L/P_N$ [%]	Efficiency $\eta$ [%]
P <sub>1</sub>	90	100	13.5	87.0
P <sub>2</sub>	50	100	11.1	81.8
P <sub>3</sub>	25	100	10.6	70.2
P <sub>4</sub>	90	50	7.1	86.4
P <sub>5</sub>	50	50	5.2	82.9
P <sub>6</sub>	50	25	4.0	75.9
P <sub>7</sub>	25	25	2.6	70.3

### MAP OF RELATIVE POWER LOSSES $P_L/P_N$ [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

\*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

\*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EL112M4D-PD-B0-000

### Torque and Current Curves Related to Speed



Motor Code : 3EL112M4D-PD-B0-000

### Performance Curves Related to Rated Output

